





● U-PVC PIPE(ESLON VP, VU) JIS K 6741



- Excellent corrosion resistance.
- Durable flow rate with smooth inner surface as no scale or rust.

Size

Unit:mm

Size	Tolerance D	t			d			L	Weight(kg/m)		
		VP	VU	HI	VP	VU	HI		VP	VU	HI
40	48±0.2	3.6+0.8	1.8+0.4	—	40	44	—	4000±10	0.791	0.413	—
50	60±0.2	4.1+0.8	1.8+0.4	—	51	56	—		1.122	0.521	—
65	76±0.3	4.1+0.8	2.2+0.6	—	67	71	—		1.445	0.825	—
75	89±0.3	5.5+0.8	2.7+0.6	—	77	83	—		2.202	1.159	—
100	114±0.4	6.6+1.0	3.1+0.8	—	100	107	—		3.409	1.737	—
125	140±0.5	7.0+1.0	4.1+0.8	—	125	131	—		4.464	2.739	—
150	165±0.5	8.9+1.4	5.1+0.8	—	146	154	—		6.701	3.941	—
200	216±0.7	10.3+1.4	6.5+1.0	10.3+1.4	194	202	194		10.129	6.572	10.338
250	267±0.9	12.7+1.8	7.8+1.2	12.7+1.8	240	250	240		15.481	9.758	15.781
300	318±1.0	15.1+2.2	9.2+1.4	15.1+2.2	286	298	286		21.962	13.701	22.494
350	370±1.2	—	10.5+1.4	—	—	348	—		—	18.051	—
400	420±1.3	—	11.8+1.6	—	—	395	—		—	23.059	—
450	470±1.5	—	13.2+1.8	—	—	442	—		—	28.875	—
500	520±1.6	—	14.6+2.0	—	—	489	—		—	35.346	—
600	630±3.2	—	17.8+2.8	—	—	592	—	—	52.679	—	

1. 350~600A : Only VU Pipe is available.

2. Weight is calculated with specific gravity HI-VPW-G: 1.40, VPW: 1.43 for reference.