



ESLON CPVC PIPE AND FITTINGS (ESLON HT)



- For high temperature application.
- Excellent durability and thermal insulation.

Size (JIS K 6776)

Unit:mm

Size	D	Tolerance		t	d	L	Weight (kg/m)	Standard	
		Max/min	Average					JIS	SEKISUI
13	18.0	±0.20	±0.20	2.5±0.20	13.0	4000±10	0.180	○	—
16	22.0	±0.20	±0.20	3.0±0.30	16.0		0.265	○	—
20	26.0	±0.20	±0.20	3.0±0.30	20.0		0.321	○	—
25	32.0	±0.20	±0.20	3.5±0.30	25.0		0.464	○	—
30	38.0	±0.30	±0.20	3.5±0.30	31.0		0.561	○	—
40	48.0	±0.40	±0.20	4.0±0.30	40.0		0.818	○	—
50	60.0	±0.40	±0.20	4.5±0.40	51.0		1.161	○	—
65	76.0	±0.40	±0.20	5.0±0.50	66.0		1.651	—	○
75	89.0	±0.40	±0.25	5.8±0.50	77.4		2.244	—	○
100	114.0	±0.50	±0.25	7.0±0.60	100.0		3.483	—	○
125	140.0	±0.60	±0.40	8.2±0.60	123.6		5.025	—	○
150	165.0	±0.80	±0.45	9.7±0.70	145.6		7.004	—	○

·Weight is calculated with specific gravity HT: 1.48 for reference.
 ·Length : 400±10
 Color : Dark brown

Product List Fitting(JIS K 6777)

Product Size	Socket	Reducing Elbow	90°Elbow	45°Elbow	Tee	Reducing Tee	Cap	11 1/4" Bend	22 1/2" Bend	45°Bend	90°Bend	Expansion Joint
13	○	—	○	○	○	—	○	○	○	○	○	○
16	○	○	○	○	○	○	○	○	○	○	○	○
20	○	○	○	○	○	○	○	○	○	○	○	○
25	○	○	○	○	○	○	○	○	○	○	○	○
30	○	○	○	○	○	○	○	○	○	○	○	○
40	○	○	○	○	○	○	○	○	○	○	○	○
50	○	○	○	○	○	○	○	○	○	○	○	○
65	○	○	○	○	○	○	—	○	○	○	○	○
75	○	○	○	○	○	○	—	○	○	○	○	○
100	○	○	○	○	○	○	—	○	○	○	○	○
125	○	○	○	○	○	○	—	○	○	○	○	—
150	○	○	○	○	○	○	—	○	○	○	○	—

·For over 200A, please refer page 47 and 48.

Product List Insert Fitting

Product Size	Insert Faucet Socket	Insert Faucet Elbow	Insert Faucet Long Elbow	Insert Faucet Tee	Insert Valve Socket
13	○	○	○	○	○
16	○	○	—	—	○
20	○	○	—	—	○
20×13	○	○	—	—	—
25	○	○	—	—	○
30	—	—	—	—	○
40	—	—	—	—	○
50	—	—	—	—	○

·For maximum working pressure, please refer page 44.